

Basic Info.

Model NO.	UL3135
Certification	ISO9001, CE, UL, RoHS
Rated Voltage	600V
Color	White, Black, Red, Brown, Yellow, Blue etc
Transport Package	Cartons
Origin	China

Range of Application	FT2
Brand	Mysun
Rated Temp	200c
Trademark	MYSUN
Specification	26-12AWG 0.3-2.5MM
HS Code	8544492900

Product dimensions:

Conductor			Insulation		Max.cond resistance (Ω/km)	Unit Length (m)(Ft)
Size (AWG)	Construction (No./mm)	Diameter (mm)	Nominal Thickness (mm)	Diameter (mm)		
26	7/0.16	0.48	0.78	2.04	143	305/1000
24	7/0.20	0.61		2.17	89.3	
22	7/0.254	0.77		2.33	56.4	
20	7/0.31	0.94		2.50	35.2	
18	7/0.39	1.19		2.75	22.2	
16	7/0.49	1.49		3.05	14	
24	11/0.16	0.61		2.17	89.3	
22	17/0.16	0.76		2.32	56.4	
20	26/0.16	0.94		2.50	35.2	
18	41/0.16	1.18		2.74	22.2	
16	26/0.254	1.49		3.05	14	
14	41/0.254	1.87		3.43	8.78	
12	19/0.47	2.36		3.92	5.53	
0.30mm ²	12/0.18	0.71		2.27	59.78	
0.50mm ²	20/0.18	0.92		2.48	40.1	
0.75mm ²	30/0.18	1.13		2.69	26.7	
1.00mm ²	40/0.18	1.31		2.87	20	
1.25mm ²	50/0.18	1.46		3.02	14.35	
2.00mm ²	41/0.254	1.87		3.43	8.78	
2.50mm ²	50/0.254	2.08		3.64	7.16	



High and Low temperature resistance



High voltage resistance



Good flame retardant



Soft and Flexible



Low Eccentricity