

Terminales de Conexión TB TC

Especificaciones



-TB



TC

Tipo	Corriente	No. de polos	Dimensiones (mm)								
			L	L	A	B	C	D	E	F	G
TB-1503	15A	3	46	36.5	7.5	9	M3	22	17		
TB-1504		4	55	45.5	7.5	9	M3	22	17		
TB-1506		6	73	63.5	7.5	9	M3	22	17		
TB-1512		12	127	118	7.5	9	M3	22	17		
TB-2503	25A	3	50	40	10.5	12	M4	30	20		
TB-2504		4	62.5	57	10.5	12	M4	30	320		
TB-2506		6	91	81.5	10.5	12	M4	30	20		
TB-2512		12	163	153	10.5	12	M4	30	20		
TB-3503	35A	3	50	40	10.5	12	M4	30	20		
TB-3504		4	62.5	57	10.5	12	M4	30	20		
TB-3506		6	91	81.5	10.5	12	M4	30	20		
TB-3512		12	163	153	10.5	12	M4	30	20		
TB-4503	45A	3	70	60.5	15	17	M5	38	23.5		
TB-4504		4	86	75.5	15	17	M5	38	23.5		
TB-4506		6	120.5	110	15	17	M5	38	23.5		
TB-6003	60A	3	70.5	65.5	15.5	18	M6	38	31		
TB-6004		4	93.5	82.5	15.5	18	M6	38	31		
TB-6006		6	129	118	15.5	18	M6	38	31		
TB-10003	100A	3	86.5	75.5	22	20	M6	43.5	35		
TB-10004		4	108	96	22	20	M6	43.5	35		
TB-10006		6	153	140	22	20	M6	43.5	35		
TC-603	60A	3	28.5	86.5	38	42.7	25.5	31	15	17	M6
TC-604		4	28.5	115	38	42.7	25.5	31	15	17	M6
TC-1003	100A	3	34.5	113.5	46.5	55.2	28	36.3	17.3	22.5	M6
TC-1004		4	34.5	137.5	46.5	55.2	28	36	17.3	22.5	M6
TC-1503	150A	3	38.5	115	57.2	67	30.5	340	19.8	25.3	M8
TC-1504		4	38.5	153	57.2	67	30.5	40	19.8	25.3	M8
TC-2003	200A	3	44.5	133	63	72.1	34	44.4	23	28.3	M8
TC-2004		4	44.5	177	63	72.1	34	44.4	23	28.3	M8
TC-3003	300A	3	55	164	78	89.4	47.5	50.6	27	30	M10
TC-3004		4	55	218	78	89.4	47.5	50.6	27	30	M10
TC-4003	400A	3	55	164	78	89.4	47.5	50.6	27	36	M10
TC-4004		4	55	218	78	89.4	47.5	50.6	27	36	M10

